



Location of Checking Points

- A Bonnet to frame top mounting, see Fig. 13 C Seat well mounting to frame, see Fig. 5 E Rear damper mounting to frame
 B Toe board mounting to frame, see Fig. 4 D Rear seat mounting to frame, see Fig. 6

Fig. 1. Chassis frame dimensions Refer to page 5-404 for Spitfire Mk. 3

Key to Fig. 1

	Inches	Centimetres		Inches	Centimetres		Inches	Centimetres
1	22-15	59-69	19	14-51	36-86	39	1-13	2-87
	22-10	58-42		14-48	36-78	40	2-80	7-11
2	14-56	36-98	20	21-03	53-39	41	83-26	211-48
3	13-78	35-00		20-97	53-27	42	31-45	79-88
	13-72	34-85	21	3-02	7-67		31-39	77-73
4	8-64	21-89		2-98	7-56	43	1-06	2-69
5	9-78	24-84	22	3-23	8-20	44	4½°	4½°
	9-72	24-69		3-12	8-15	45	0-26	0-66
6	5-55	14-05	23	2-91	7-37	46	11-69	29-69
	5-50	13-97		2-89	7-24		11-56	28-36
7	4-32	10-97	24	7-19	18-26	47	25-59	65-00
	4-30	10-92		7-13	18-11		25-47	64-69
8	17-37	44-12	25	4-25	10-80	48	4½°	4½°
	17-25	43-91	26	7-83	19-86	49	1-00	2-54
9	12-78	32-36		7-80	19-81	50	5-32	12-76
	12-72	32-31	27	6-64	16-87		5-26	12-77
10	16-09	40-87		6-61	16-79	51	13-06	33-17
	16-03	40-72	28	10-70	27-18		12-94	32-87
11	29-62	75-13		10-65	27-05	52	5-91	15-01
	29-50	74-77	29	1-51	3-83	53	7-31	18-50
12	36-56	92-86	30	1-63	4-14	54	6-29	15-97
	36-44	92-56		1-61	4-09		6-17	15-67
13	42-19	107-16	31	11-78	29-92	55	6-71	17-06
	41-94	104-83		11-72	29-77		6-59	16-74
14	68-22	173-28	32	14-75	37-46	56	6-22	15-80
	68-10	172-97	33	6-22	15-80	57	5-13	13-01
15	87-19	221-46	34	12-00	30-48	58	.78	1-98
	86-93	220-80	35	0-15	0-38	59	14-53	36-90
16	10-32	26-21	36	5-00	12-70		14-47	36-76
17	5-39	13-69		4-88	12-40	60	23-31	59-21
	5-36	13-61	37	1-12	2-87		23-19	58-90
18	5-23	13-28		1-00	2-54	61	2-95	7-50
	5-20	13-20	38	4-06	10-31		2-82	7-08